an image processing unit coupled to said memory for executing the program

instructions stored in said memory;

wherein (a) said image sensor generates at least one more row and column of pixels

then the image processing unit processes or (b) an image capture unit

generates at least one additional row and column of pixels for said captured

image data from said image sensor.

37. A digital image capture device, comprising:

an image sensor, for generating image data;

an orientation sensor, for automatically sensing the orientation of the image sensor

relative to a reference orientation and generating an orientation signal

indicating the orientation of the image sensor relative to the reference

orientation; and

an auto-rotate unit coupled to the image sensor and the orientation sensor, for

automatically rotating the image data in response to the orientation signal.

38. The digital image capture device of claim 37, further comprising:

an image processing unit coupled to the auto-rotate unit, for processing a subset of the

rotated image data.

39. The digital image capture device of claim 37, further comprising:

an image capture unit coupled to the image sensor, for adding m additional rows and

n additional columns to an i-by-j array of image data to form an i+m-by-j+n

array of image data to be rotated by the auto-rotate unit in response to the

orientation signal.

40. A method of rotating image data in a digital image capture device, comprising:

capturing image data from an image sensor;

automatically sensing the orientation of the image sensor relative to a reference

orientation;

providing an orientation signal indicating the orientation of the image sensor relative
to the reference orientation; and
automatically rotating the captured image data in response to the orientation signal.

41. The method of claim 40, wherein the rotating step further comprises:
automatically rotating a subset of captured image data in response to the orientation
signal.

42. The method of claim 40, further comprising:
adding m additional rows and n additional columns to an i-by-j array of the image
data to form an i+m-by-j+n array of image data to be rotated by the auto-rotate
unit in response to the orientation signal.

43. A computer-readable medium having stored thereon instructions which, when
executed by a processor, cause the processor to perform the steps of:
capturing image data from an image sensor;
automatically sensing the orientation of the image sensor relative to a reference
orientation;
providing an orientation signal indicating the orientation of the image sensor relative
to the reference orientation; and
automatically rotating the captured image data in response to the orientation signal.

44. The computer-readable medium of claim 43, wherein the rotating step further
comprises:
automatically rotating a subset of captured image data in response to the orientation
signal.

45. The computer-readable medium of claim 43, further comprising:

adding m additional rows and n additional columns to an i-by-j array of the image data to form an i+m-by-j+n array of image data to be rotated by the auto-rotate unit in response to the orientation signal.

46. A digital image capture device, comprising:

means for generating image data;

means for automatically sensing the orientation of the image sensor relative to a reference orientation;

means for generating an orientation signal indicating the orientation of the image sensor relative to the reference orientation; and

means for automatically rotating the image data in response to the orientation signal.

STATUS OF CLAIMS AND SUPPORT FOR CLAIM CHANGES

Original claims 1-35 are in the patent as issued and new claims 36-46 are pending. Support for new claims 36-46 can be found in the specification of the issued patent at cols. 3-13 *et seq*.

Respectfully submitted,

ERIC C. ANDERSON

Dated: January 4 , 2002   By: _____

Kirk A. Gottlieb, Reg. No. 42,596
Attorney for Applicants
Fenwick & West LLP
Two Palo Alto Square
Palo Alto, CA 94306
Tel.: (415) 875-2414
Fax: (415) 281-1350

18602/06614/SF/5065151.1